

3380879

WPL610

BARCODE PRINTER



Big Business Tools. Small Business Attitude.

SPECIFICATIONS

Standard Features

PRINTING METHOD	Thermal transfer and direct thermal
RESOLUTION	203 dpi (8 dots / mm)
PRINT SPEED	Up to 12 inches per second
MAX. PRINT WIDTH	4.09" (104 mm)
MAX. PRINT LENGTH	160" (4064 mm)
MEMORY	32 MB SDRAM 8 MB Flash
SENSORS	Position adjustable transmissive/reflective sensor, ribbon end sensor, head open sensor
CABINET	Metal construction with clear plastic media view window
OPERATION PANEL	128 x 64 pixel with backlight
DIMENSIONS	10.63" (W) x 12.13" (H) x 19.88" (D) or 270 mm (W) x 308 mm (H) x 505 mm (D)
NET WEIGHT	33 lbs (15 kg)
COMMAND SET	WPL, ZPL emulation, EPL emulation

Operational Characteristics

COMMUNICATION	Internal Ethernet, USB 2.0, RS232, Centronics Parallel
INTERFACES	
OPERATING TEMPERATURE	40°F to 104°F (5°C to 40°C)
STORAGE TEMPERATURE	23°F to 140°F (-5°C to 60°C)
CERTIFICATIONS	FCC, CE, C-Tick, UL, CUL, TUV/GS, CCC, CB, ROHS

Media

MEDIA WIDTH	1" to 4.6" (25.4 to 118 mm)
MEDIA DIAMETER	8" OD (203 mm) with 1", 3" core (25 mm, 76 mm core)
RIBBON LENGTH	1968 ft (600 meters)

Fonts, Graphics & Symbologies

BARCODE SYMBOLOGIES	1D Barcodes: Code 39, Code 93, Code 128 UCC, Code 128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST 2D Barcodes: PDF-417, Maxicode, Datamatrix, QR code
RESIDENT FONTS	8 alpha-numeric bitmap fonts Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font
FONT ROTATION	0, 90, 180, 270 degree

Options & Accessories

MEMORY EXPANSION	SD Memory expansion slot for use with 4 GB SD cards
CUTTER	4" width (paper thickness up to 0.25 mm)
PEEL & PRESENT	Included
INTERNAL ETHERNET PRINT SERVER	Included