



wasp
BARCODE TECHNOLOGIES



WDI4250 | 2D USB Barcode Scanner

Durable Handheld Barcode Scanner Ideal for High Efficiency Applications



Key Features

- Superior scanning
- LED-based technology with extreme precision aiming system
- 'Green Spot' technology for superior good-read feedback
- Motionix™ patented motion-sensing technology for seamless reading mode transitions
- Omnidirectional (with optional stand) reading for 1D, 2D, postal codes, stacked and composite bar codes and dot codes
- USB Type A/USB only
- Aladdin™ 3.0 configurator provides the latest GUI, search engines, and an on-line version that offers the ability to generate programming barcodes to scan directly on a smartphone

WDI4250 | 2D USB Barcode Scanner

OPTIC AND PERFORMANCE

Aiming: Blue LED emission 468 nm
Illumination: Red LED emission 617 nm
Image Capture: Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
Image Sensor: VGA (640 x 480 pixels)
Motion Tolerance: 30 IPS
Resolution: 1D Linear: 0.077 mm / 3 mils; PDF417: 0.127 mm / 5 mils; Data Matrix: 0.152 mm / 6 mils; QR Code: 0.17 mm / 6.7 mils
Scan Angle: Pitch: +/- 65°; Roll (Tilt): +/- 360°; Skew (Yaw): +/- 65°
Print Contrast Ratio: minimum 15% with specific configuration
Reading Indicators: Beeper (Adjustable Tone and Volume); 'Green Spot' Good-read feedback on the code; Good-read LED

DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.
Code 39: 5 mils: 0.5 to 23.0 cm / 0.2 to 9.0 in
Code 39: 10 mils: 0.5 to 37.0 cm / 0.2 to 14.5 in
Data Matrix: 10 mils: 1.0 to 15.5 cm / 0.39 to 6.1 in
EAN/UPCA: 13 mils: 1.0 to 40.0 cm / 0.39 to 15.7 in
PDF417: 6.7 mils: 0.5 to 13.5 cm / 0.2 to 5.3 in
QR Code: 20 mils: 1.0 to 33.0 cm / 0.39 to 12.9 in

PHYSICAL CHARACTERISTICS

Dimensions (scanner only): 6.2 x 2.7 x 4.2 in (15.9 x 6.8 x 10.7 cm)
Scanner Weight: 5.0 oz. (145.0 g.)
Color: Black
Connector: USB
Trigger: Scan button
Indicator: Beeper (Adjustable Tone and Volume), green spot for good-read feedback and good read LED

CONNECTIVITY

USB Type A / USB

USER ENVIRONMENT

Operating Temperature: 32~122°F (0~50°C)
Storage Temperature: -40~158°F (-40~70°C)
Humidity: 0%~95% (non-condensing)
Drop Durability: 5 ft. (1.5 m)
Particulate and Water Sealing: IP52
Ambient Light: Up to 110,000 lux
Trigger Resistance: Withstands 10 Mhits
ESD Protection (Air Discharge): 16kV
Symbolologies: Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot code. Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Postnet; Royal Mail Code (RM4SCC). EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites.

REGULATORY

ESD Protection (Air Discharge): 16 kV
LED Classification: Illuminator Exempt group, Aiming Risk Group 1 according to IEC 62471
Agency Approvals: The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
Environmental: Complies to China RoHS; Complies to EU RoHS

ACCESSORIES

WaspProtect Extended Warranty (SKU 633809002984)
Wasp WDI4250 Stand (SKU 633809013461)



Wasp North America

3001 Summit Avenue
Suite 400
Plano, TX 75074
1-866-547-9277
www.waspbarcode.com

Wasp Europe

Dunstable Road
Redbourn, St Albans
AL3 7PR, UK
0845-430-1971
www.waspbarcode.co.uk

Wasp International

+1 214-547-4100