



**wasp**  
BARCODE TECHNOLOGIES



**WWS752** | Wireless 2D Scanner

## Ultra-Rugged 2D Scanner Built for Demanding Warehouse and Industrial Environments



### Key Features

- Reads 1D and 2D barcodes from a few inches to 65 feet away
- Ultra-rugged design with IP65/IP67 protection and 6.6 ft drop resistance
- Long-lasting 3350 mAh battery supports 80,000+ scans per charge
- Bluetooth 5.0 wireless range up to 328 feet
- Ergonomic, balanced design reduces strain during all-day use
- Reliable performance on damaged, poorly printed, or shrink-wrapped barcodes

# WWS752 | Wireless 2D Scanner

<b>CONNECTIVITY</b>	Radio Frequency: 2.4 GHz. Profiles: SPP (Serial Port Profile) and HID (Human Interface Device); Protocol: Bluetooth 5.0 Certified. Class 1, Class 2 and Class 3; Radio Range from the base station (Open Air): 100.0 m / 328.0 ft Security: Data Encryption; Scanner Authentication
<b>ELECTRICAL CHARACTERISTICS</b>	Current: Operating 480 mA @ 3.7 V; Charging (Typical) < 15 W Battery: Lithium-Ion: 3350 mAh; Charge Time @ 12 VDC: 2.5 hours to charge up to 95%; 3.2 hours to charge 100%, External Power. Reads per Charge: 80,000+ Input Voltage: Host powered: 5V DC $\pm$ 5% or 10 - 30 VDC; External power supply: 10 - 30 VDC $\pm$ 5%
<b>PHYSICAL CHARACTERISTICS</b>	Dimensions: 7.8" H x 5.9" L x 3.1" W (19.7 cm H x 14.9 cm L x 7.9 cm W) Net weight (scanner only): 14.6 oz (.41 kg) Shipping weight (boxed): 4.8 lbs (2.18 kg) Interfaces: RS-232 / USB / Ethernet and Industrial Protocols
<b>ENVIRONMENTAL CHARACTERISTICS</b>	Ambient Light: 0 - 100,000 lux Operating temperature: -4°F to 122°F (-20° to 50°C) Storage temperature: -40°F to 158°F (-20°C to 50°C) Humidity: 0% to 95% (non-condensing) Drop resistance: Withstands 50 drops from 6.6 ft (2.0m) Trigger resistance: Withstands 10 million hits Particulate and Water Sealing: IP67 and IP65 ESD Protection (Air Discharge): 20 kV
<b>SAFETY CERTIFICATIONS</b>	Agency Approvals: The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. Environmental Compliance: Complies to China RoHS; Complies to EU RoHS; Complies to R.E.A.C.H. Laser Classification: Caution Laser Radiation - Do not stare into beam; CDRH Class II; IEC 60825 Class 2 LED Classification: IEC 62471 Class 1 LED
<b>SYBLOGIES READ</b>	1D / Linear Codes: Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. 2D Codes: Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot Code Postal Codes: Australian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post Stacked Codes: EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites
<b>READING PERFORMANCE</b>	Imager Sensor: 1280 x 800 pixels Light source: Aiming: 650 nm VLD; Illumination: Red LED reading light Print Contrast Ratio (Minimum): 20% Reading Angle: Pitch: +/- 60°; Roll (Tilt): 360°; Skew (Yaw): +/- 60° Reading Indicators: Beeper (Adjustable Tone and Volume); Dual Good Read LEDs; Vibration. Resolution (Maximum): 1D Codes: 2.5 mil; 2D Codes: 5 mil
<b>READING RANGES</b>	Typical Depth of Field: Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. Code 39 3 mils: up to 37 in / 95 cm; Code 39 20 mils: up to 236 in / 600 cm; EAN/UPC 13mils: up to 126 in / 320 cm; Code 128 40 mils: up to 393 in / 1000 cm; Code 128: 100 mils: up to 787 in / 2000 cm; Data Matrix 10 mils: up to 43 in / 110 cm; Data Matrix 55 mils: up to 256 in / 650 cm; Data Matrix 100 mils: up to 393 in / 1000 cm
<b>PART NUMBERS</b>	Wasp WWS752 Wireless 2D Scanner (I00009450) Wasp WWS752 Wireless 2D Scanner with RS232 (I00009488) Wasp WWS752 Battery Pack, Removable (I00009485) Wasp WWS752 RS232 Cable, 6' (I00009486) WWS650/WWS652/WWS750/WWS752 Power Supply, Includes Power Adapter and Cord (633809005794) UK WWS650/WWS652/WWS750/WWS752 Power Supply (633809008238) WaspProtect WWS750/WWS752 48Hr 2Yr (633809003202) - US only WaspProtect WWS750/WWS752 48Hr 3Yr (633809009747) - US only



**Wasp North America**  
3001 Summit Avenue  
Suite 400  
Plano, TX 75074  
1-866-547-9277  
[waspbarcode.com](http://waspbarcode.com)

**Wasp Europe**  
Dunstable Road  
Redbourn, St Albans  
AL3 7PR, UK  
0845-430-1971  
[waspbarcode.co.uk](http://waspbarcode.co.uk)

**Wasp International**  
+1 214-547-4100