



wasp
BARCODE TECHNOLOGIES



WDT960 | 2D Android Mobile Computer

Rugged Handheld Built For Fast, Accurate Barcode Scanning In Demanding Environments



Key Features

- Android 14 OS with GMS and AER certification
- 2D barcode scanning from up to 3 feet away
- Bright green laser aimer for accurate barcode targeting
- Wi-Fi 6E and Bluetooth® 5.2 connectivity
- IP65/IP67-rated protection against dust and water
- 1.8-meter drop resistance, up to 2.4 meters with bumper
- 38-key backlit numeric keypad for fast data entry
- 30-degree tilt-down scanning design for more comfortable use

WDT960 | 2D Android Mobile Computer

OPERATING SYSTEM	OS: Android 14, GMS and AER CPU: Qualcomm Snapdragon™ 4490 Processor, 64bits, Octa Cores up to 2.4GHz Memory: 6GB RAM + 128GB UFS Flash Languages support: Multi-languages
COMMUNICATION	Bluetooth: Bluetooth® 5.2 WLAN: Wi-Fi 6E, 2.4GHz & 5GHz & 6GHz; IEEE 802.11a/b/g/n/ac/d/h/i/k/r/v/ac/ax (MIMO 2X2); Support DBS & Fast roaming; Security WPA3, WPA2, WPA & WEP Sensors: Gyroscope, G-sensor, E-compass, Light & Proximity Sensor, 3-axis accelerometer
ELECTRICAL CHARACTERISTICS	Main Battery: 3.6V 6700mAh Hot Swap Battery: Keeps applications active up to 1 minute
PHYSICAL CHARACTERISTICS	Dimensions: 7.68" H x 2.83" L x 1.34" W (19.5 cm H x 7.2 cm L x 3.4 cm W) Net weight (scanner with battery only): .87 lb (.39 kg) Shipping weight (boxed): 1.25 lbs (.57 kg) Interfaces: USB Type C Connector for PC. POGO PIN OTG connector for Cradle. Expansion Slot: Micro SD/TF x 1 (Support SD, SDHC and SDXC), up to 256GB Audio: Speaker: 2W output, One speaker with Smart PA (105 dB at 10cm) MIC: Dual-Microphone, support noise cancellation
DISPLAY	Screen Size: 4" TFT-LCD WVGA (480x800) color screen (400 nits) Touchpanel: Ultra-sensitive capacitive touch screen, compatible with gloves (thickness ≤ 4 mm) and support wet resistance, stylus (3 mm)
KEYPAD	Function Numeric (38 key) with backlight
CAMERA	Rear camera: 16 MP with auto-focus and LED flash, support ARcore
ENVIRONMENTAL CHARACTERISTICS	Operating temperature: -4°F to 122°F (-20° to 50°C) Storage temperature: -22°F to 158°F (-30°C to 70°C) (without battery) Charging: 32 to 113 °F (0 to 45 °C) Relative Humidity: 5% ~ 95% (non-condensing) Drop specification: 1.8 m / 2.4 m (with bumper) Sealing: IP65 / IP67
SAFETY CERTIFICATIONS	Regulatory Approvals: CE, FCC, NCC, IC, VCCI, TELEC, CCC, SRRC, RoHS, CEC, BQB, GMS, N-Mark
SYMBOLOGIES READ	All major 1D and 2D codes
READING RANGES	Depth of Field, Approx., by symbology: 13 mil 100% UPC: 1.6 inches to 2.1 feet; 13 mil 100% UPC: 1.6 inches to 2.1 feet; 4 vs. 3 mil Code 39: 3 inches - 5.8 inches; 20 mil Code 39: 1.6 inches to 3 feet; 5 mil PDF417: 3 inches - 7.9 inches; 7 mil PDF417: 2.5 inches - 10.1 inches; 5 mil Code 128: 2.3 inches - 9.8 inches; 15 mil Code 128: 2.4 inches to 2.3 feet; 15 Mil QR Code: 1.1 inches to 1.5 feet; 10 mil DataMatrix: 2.1 inches - 11 inches.
PART NUMBERS	Wasp WDT960 2D Android Mobile Computer (I00011409) Wasp WDT960 2D Android Mobile Computer Cradle (I00011410) WDT960 with Charging Cradle, and Power Supply w/US Power Cord Bundle (I00011442) WDT960 W/UK Power Supply bundle - EUR (I00011562) WaspProtect 3-Year Extended Service Plan WDT960 (I00011561) – US Only



Wasp North America
3001 Summit Avenue
Suite 400
Plano, TX 75074
1-866-547-9277
waspbarcode.com

Wasp Europe
Dunstable Road
Redbourn, St Albans
AL3 7PR, UK
0845-430-1971
waspbarcode.co.uk

Wasp International
+1 214-547-4100